

BIMETALLIC DIAL THERMOMETERS

- All stainless steel construction IP65 case
- White dial face with large easy to read graduations
- Calibration Reset at rear of case
- Accuracy = 1% of full scale
- Safety Glass or Perspex Face available



SD 030

Model BA 5

**Bimetal Thermometer
5" Dial Every angle**

1/2" NPT Fixed Thread.

18 x Temperature Ranges
From - 50 to 50 Deg C
Up to 0 to 600 Deg C

Stem Length including thread
2.5", 4", 6", 9", 12", 15" & 18"

*Specify temperature range
and stem length with order*



Model BA 3

**Bimetal Thermometer
3" Dial Every angle**

1/2" NPT Fixed Thread

18 x Temperature Ranges
From - 50 to 50 Deg C
Up to 0 to 600 Deg C

Stem Length including thread
2.5", 4", 6", 9", 12", 15" & 18"

*Specify temperature range
and stem length with order*



SD 029

Model BL 3

**Bimetal Thermometer
3" Dial Back Connection**


1/2" NPT Fixed Thread

18 x Temperature Ranges
From - 50 to 50 Deg C
Up to 0 to 600 Deg C

Stem Length including thread
2.5", 4", 6", 9", 12", 15" & 18"

*Specify temperature range
and stem length with order*

For additional information and pricing.



TEMPERATURE CONTROLS PTY LTD

Sydney: 7 Yamma St Sefton NSW 2162 T (02) 9721 8644 F (02) 9738 9339
Melbourne: 8/280 Whitehall St Yarraville VIC 3013 T (03) 9687 0000 F (03) 9687 1900
W www.temperature.com.au E sales@temperature.com.au

Due to ongoing product development, specification and price may change without notice.

Prices do not include GST