

# DIGITAL THERMOMETERS

- All stainless steel 100 mm diameter IP65 case
- Battery powered ( Approx 3 years life 2 x 1.5VAA)
- 3 wire RTD PT 100 Input
- 13 mm High 3 1/2 LCD Display
- Accuracy = 0.25 % of full scale



SD 388

## Model DPT3 DM

### Indicator

Direct Mount  
Bottom Entry Shown  
Optional Centre rear entry

Temperature Ranges  
-50 Deg C to 199.9 Deg C  
0 to 500 Deg C x 1 Deg

Low Battery Indication  
M16 x 1.5 Cable Entry



SD 388

## Model DPT3 SM

### Indicator

Surface Mount Flange  
Bottom Entry Shown  
Optional Entries available

Temperature Ranges  
-50 Deg C to 199.9 Deg C  
0 to 500 Deg C x 1 Deg

Low Battery Indication  
M16 x 1.5 Cable Entry



Loop powered Transmitter  
Analogue Output 4—20 mA  
Loop Powered 10—32 V

## Model DPT420-S

### Indicator & Transmitter

Surface Mount Flange  
Bottom Entry Shown  
Optional Entries available

Temperature Ranges  
-50 Deg C to 199.9 Deg C  
0 to 500 Deg C x 1 Deg

Low Battery Indication  
M16 x 1.5 Cable Entry

*Suitable for use in food, chemical and pharmaceutical Industries.*

*For additional information and pricing.*



## TEMPERATURE CONTROLS PTY LTD

**Sydney:** 7 Yamma St Sefton NSW 2162 T (02) 9721 8644 F (02) 9738 9339  
**Melbourne:** 8/280 Whitehall St Yarraville VIC 3013 T (03) 9687 0000 F (03) 9687 1900  
**W** [www.temperature.com.au](http://www.temperature.com.au) **E** [sales@temperature.com.au](mailto:sales@temperature.com.au)

Due to ongoing product development, specification and price may change without notice.

Prices do not include GST