## TEMPERATURE CONTROLS PTY LTD

ACN: 650 190 183 ABN: 966 501 901 83 7 YAMMA STREET









THERMOCOUPLES \* RTD SENSORS \* THERMOWELLS \* EXTENSION CABLES \* LEVEL SWITCHES

SD 1398

### THERMOCOUPLE CONNECTORS

Full Size, Standard, 2-Pole

- 2-Pole Connector plugs and jacks are made to exacting specifications to (Hi-Temp Body Shown) provide rapid, dependable connections between thermocouples and extension wires.
- Alloys of prongs and inserts match ANSI calibrations to maintain sensing accuracy. Alloy and polarity are identified by symbols molded into body.
- Connector bodies molded of glass filled thermoset compounds (will not *melt*) for high strength and dependability. The color coded Connectors will withstand ambient temperatures to 400°F (205°C) continuous and 500°F (260°C) intermittent. High-Temperature Connectors (all Hi-Temp connectors are colour coded red) will withstand ambient temperatures to 800°F (425°C) continuous and 1000°F (540°C) intermittent.



- Inserts are spring loaded collet type to assure positive full contact with the negative insert larger making it virtually impossible to mismate.
- For corrosive applications, gold or nickel plated prongs and inserts are available. Caution system errors can result from use of plated contacts if significant thermal gradients exist at connector.

FULL SIZE 2-POLE	
Marlin Code No.	Description
1060 - *	Plug
1050 - <sup>†</sup>	Solid Pin Plug
1010 - *	Jack
FULL SIZE HIGH-TEMPERATURE 2-POLE	
1160 - *	Plug
1150 - <sup>†</sup>	Solid Pin Plug
1110 - *	Jack

\* - Tubular Pin Availability: J,K,T,N,E,R,S,U, also "C" † - Solid Pin Availability: J,K,T,E,R,S,U For Gold Plating use suffix "G" (i.e. 1050-K-G) For Nickel Plating use suffix "P" (i.e. 1060-K-P)

# TEMPERATURE CONTROLS PTY LTD

ACN: 650 190 183 ABN: 966 501 901 83 7 YAMMA STREET SEFTON, NSW 2162 AUSTRALIA



PH: (02) 9721 8644 FAX: (02) 9738 9339 EMAIL: <a href="mailto:sales@temperature.com.au">sales@temperature.com.au</a> www.temperature.com.au

THERMOCOUPLES \* RTD SENSORS \* THERMOWELLS \* EXTENSION CABLES \* LEVEL SWITCHES

## MOUNTING HARDWARE FOR 2-POLE CONNECTOR

#### **Nickel Plated Construction**

All screws mount from top into threaded bottom plate (no loose nuts).

CABLE CLAMP		
Code No.	1080	
Code No.	1088 w/mtg. stud	
WIRE CLAMP		
Code No.	1084	
Code No.	1085 w/mtg. stud	
CRIMP ADAPTER		
Code No.	1074-125	
Code No.	1074-187	
Code No.	1074-250	
COMPRESSION ADAPTER		
(metal sheathed T/C to connector)		
Code No.	1070-*	
Code No.	1078-* w/mtg. stud	
COMPRESSION ADAPTER-DUAL		
(metal sheathed T/C to connector)		
Code No.	1071-*	

<sup>\* -</sup> Specify Size Code: 000(Blank - No nut or ferrule), 040 (0.040"), 062 (0.062"), 125 (0.125"), 187 (0.187"), 250 (0.250"), 312 (0.312"), 375 (0.375")