

SYDNEY: 7 YAMMA STREET SEFTON, NSW 2162 AUSTRALIA PHONE: 61 2 9721 8644 FAX: 61 2 9738 9339

MELBOURNE: 8/280 WHITEHALL STREET, VIC 3013 AUSTRALIA PHONE: 61 3 9687 0000 FAX: 61 3 9687 1900

BRISBANE: PO BOX 5138 ALEXANDRA HILLS, QLD 4161 AUSTRALIA PHONE: 61 0418 222 868 FAX: 61 7 3821 3693

INTERNET: www.temperatureshop.com.au

EMAIL: sales@temperature.com.au

STATOR RTD SENSORS

Stator winding style RTD's are suitable for use where a temperature rating up to 200°C is required. Typically the stator or slot elements are inserted between the coils in the stator of an electric motor. These averaging type sensors are used in large electric motors and generators for continuous sensing of the internal temperature and provide for consistent thermal monitoring without false alarms.

Part Number	Description	Part Number	Description
TCPSTATOR2002T	Class B PT100 OHM 3 wire 200mm x 6.7 x 2.3 C/W 2 meter 3 core Teflon Tails Temperature Range -50C to 180C	TCPSTATOR1502T	Class B PT100 OHM 3 wire 150mm x 6.7 x 2.3 C/W 2 meter 3 core Teflon Tails Temperature Range -50C to 180C

