

STANDARD - NO or NC CONTACT RATED AT 32V AC/DC @ 500mA RESISTIVE LOAD

CHANGE OVER CONTACT


1/2" BSPP 1" BSPT 1" BSPP 1" NPT

NOTE: IF THE THREAD IS PARALLEL
(SPECIFY THREAD LENGTH X)

PROCESS CAPABILITIES - SUITABLE FOR DIESEL

- STAINLESS STEEL / NBR PLASTIC CONSTRUCTION / BRASS COLLARS
- UP TO 5 FLOATS PER ASSEMBLY MAXIMUM LENGTH 1800mm
- INDIVIDUAL OR COMMON CIRCUIT WIRING
- SPECIAL THREADS AND LENGTHS AVAILABLE
- SPECIFIC GRAVITY 0.5
- TEMPERATURE RATING 100°C MAXIMUM
- PRESSURE RATING :ATM means atmosphere pressure.
Pressure rating is atmosphere pressure.
i.e. cannot be used in pressurized environment
- SCREW IN MULTI -LEVEL ASSEMBLY
- 18.5mm DIAMETER NBR PLASTIC FLOAT

FLOAT DIMENSIONS



TEMPERATURE CONTROLS PTY LTD		QUALITY ENDORSED COMPANY Certificate No: QEC 14412 AS/NZS 9001:2008	
CONDITIONS THIS DRAWING IS OUR EXCLUSIVE PROPERTY AND MUST NOT BE COPIED OR HANDED TO ANY OTHER PARTIES WITH OUT WRITTEN PERMISSION. IT SHALL BE RETURNED UPON REQUEST	SYDNEY: 7 YAMMA ST SEFTON NSW 2162 PHONE: (02) 9721 8644 FAX: (02) 9738 9339 MELBOURNE: 8/280 WHITEHALL ST YARRAVILLE VIC 3013 PHONE: (03) 9687 0000 FAX: (03) 9687 1900 BRISBANE: 28A/125 KERRY RD ARCHERFIELD QLD 4108 PHONE: (07) 3373 8424 FAX: (07) 3373 8067 EMAIL: sales@temperature.com.au		
	TITLE		
	SIZE : A4	DATE : 30/09/15	DWG NO : SD 778
	SCALE : NTS	DRAWING BY R.B	REV : 02