


- STANDARD - NO or NC CONTACT RATED AT 32V AC/DC @ 500mA RESISTIVE LOAD
- CHANGE OVER CONTACT

**FLOAT DIMENSIONS**



**PROCESS CAPABILITIES - SUITABLE FOR DIESEL**

- STAINLESS STEEL / NBR PLASTIC CONSTRUCTION / BRASS COLLARS
- UP TO 5 FLOATS PER ASSEMBLY MAXIMUM LENGTH 1800mm
- INDIVIDUAL OR COMMON CIRCUIT WIRING
- SPECIAL THREADS AND LENGTHS AVAILABLE
- SPECIFIC GRAVITY 0.5
- TEMPERATURE RATING 100'C MAXIMUM
- PRESSURE RATING :ATM means atmosphere pressure. Pressure rating is atmosphere pressure. i.e. cannot be used in pressurized environment
- SCREW IN MULTI -LEVEL ASSEMBLY
- 18.5mm DIAMETER NBR PLASTIC FLOAT

<b>TEMPERATURE CONTROLS PTY LTD</b>		QUALITY ENDORSED COMPANY Certificate No:QEC 14412 AS/NZS 9001:2008
<b>CONDITIONS</b>		SYDNEY: 7 YAMMA ST SEFTON NSW 2162 PHONE: (02) 9721 8644 FAX: (02) 9738 9339 MELBOURNE: 8/280 WHITEHALL ST YARRAVILLE VIC 3013 PHONE: (03) 9687 0000 FAX: (03) 9687 1900 BRISBANE: 28A/125 KERRY RD ARCHERFIELD QLD 4108 PHONE: (07) 3373 8424 FAX: (07) 3373 8067 EMAIL: sales@temperature.com.au
THIS DRAWING IS OUR EXCLUSIVE PROPERTY AND MUST NOT BE COPIED OR HANDED TO ANY OTHER PARTIES WITH OUT WRITTEN PERMISSION. IT SHALL BE RETURNED UPON REQUEST		TITLE
SIZE : A4	DATE : 23/09/15	<b>DWG NO : SD 831</b>
SCALE : NTS	DRAWING BY R.B	<b>REV : 03</b>